

360 IP CAMERA

ISCP15X25



FEATURES

- 25X Optical Zoom, 8X Digital Zoom
- Day & Night (Removable IR)
- 5-megapixel CMOS sensor
- 5MP H.265/HEVC and H.264/AVC high efficiency video compression
- 3D Noise Reduction (MCTF)
- HDR up to 120dB
- 200-meter IR night vision
- Pan & Tilt
- Pan 360° without stop point
- Tilt 240°
- 2-way audio Support
- ONVIF Support
- IP66 Protection
- IK10 Impact resistance
- Rainproof glasses

INNOS TECHNOLOGIES INC.

Address: 4711 Yonge Street, 10th Floor, North York, ON M2N 6K8 Canada

Phone: +1 4374508954

Email: contact@innostech.ca

Sensor	5 megapixel CMOS image sensor
Pixels	2616 × 1964 pixels
Light Sensitivity	0.01 lux at F1.6
Optical Zoom	25X
Digital Zoom	8X
Focal Length	5.3 – 132.5 mm
Iris Range	F1.6-32
Iris Control	DC IRIS, ALC/manual
Zoom Speed	0-7 Adjustable
Convergence Speed	0-7 Adjustable
Convergence	Auto/manual
IR Wavelength	850nm
IR Beam Adjustment	Auto, depending on zoom ratio
IR Working Distance	200m
Pan	360 degrees without stop
Pan speed	Manual: 0.1°/sec – 120°/sec 8 steps; Preset: 1°/sec – 300°/sec, Alarm rate 300°/s
Tilt	-30° to +210°
Tilt speed	Manual: 0.1°/sec – 120°/sec 8 steps; Preset: 1°/sec – 300°/sec, Alarm rate 300°/s
S/N	> 50dB (AGC off)
White Balance	Auto/Manual
LAN Connectivity	Yes, 10/100 Mbps Base-T, RJ-45
PoE	Supported
Memory Card Slot	Yes
IP Rating	IK10, IP66
Power Supply (not include Adapter)	AC24V ±10% / DC24V
Operating Temperature	- 40°C to 50° C

INNOS TECHNOLOGIES INC.

Address: 4711 Yonge Street, 10th Floor, North York, ON M2N 6K8 Canada

Phone: +1 4374508954

Email: contact@innostech.ca